



IntelliTouch® Pro Projected Capacitive Touch Solutions

The Elo IntelliTouch® Pro Projected Capacitive (PCAP) touch technology offers a fast and sensitive response and professional-grade reliability combined with a stylish, sleek design. Elo IntelliTouch Pro PCAP is designed for the rigors of commercial applications. The two glass solution (2GS) offers pristine optical clarity, high touch durability and long term stability over temperature. IntelliTouch Pro is available in standard screen sizes up to 32-inches with 10-point multi-touch capabilities.


Elo offers a complete PCAP solution including touch screen, controllers, drivers for various operating systems and software utilities resulting in shorter development and integration time. The complete integration guide provides guidelines to simplify integration and avoid typical issues such as EMI from sources such as the power supply or LCD screen.

Elo also offers a wide range of customization options to meet your requirements including screen dimensions, cover glass thickness, bonding and coating such as anti-glare.


Touch Screen



Controller



**Software Drivers
and Utilities**



Benefits

- 10-point multi-touch
- Fast and sensitive touch response
- Pristine optical clarity
- Long-term stable operation over temperature
- Optional coatings such as anti-glare

Applications

- Interactive digital signage
- Gaming machines and lottery terminals
- Industrial automation
- Medical equipment
- Transportation kiosks
- Retail automation

About Elo

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

Elo IntelliTouch Pro Projected Capacitive Specifications

Touchscreen	
Size Range	7" to 32"
Light Transmittance	≥88%
Sealing	Can be sealed to meet NEMA 4, NEMA 12 and IP 65 standards
Thickness	2.4mm to 4.0mm
Durability	Over 50 million touches in one location
Cleaning	Clear glass is unaffected by cleaning solutions
Coating Options	Anti-Glare
Touch Performance	
Input Methods	Finger, gloved hand, or passive stylus
Number of Touches	Up to 10
Response Time	25ms (15ms secondary)
Report Rate	10ms
Positional Accuracy	±2.5mm
Resolution	4096 x 4096
Touch Activation Force	Zero
Electrical	
Communication Interface(s)	USB
Power Supply Voltage Requirements	5V
Current – Operating Mode	Up to 75mA
Current – Suspend/Sleep Mode	Up to 2mA
Environmental	
Touchscreen	Operating Temp 0 to 50C Operating Relative Humidity (Non Condensing) 90%
Controller	Operating Temp -20 to 60C Operating Relative Humidity (Non Condensing) 90%
Safety Approvals	UL
Software	
Operating Systems	Windows XP, Windows 7, Windows 8, Linux, Android
Utilities	Multiple monitor, various touch modes, touch zones
Warranty	
	2 year limited warranty

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000

Fax +1 408 597 8001

customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00

Fax +32 (0)16 70 45 49

elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385

Fax +86 (21) 3329 1400

www.elotouch.com.cn

Latin America

Tel 786-923-0251

Fax 305-931-0124

www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2013 Elo Touch Solutions, Inc. All rights reserved. DS000081, rev F 09/14

