

New models of 15" and 17" LED backlight Touch Monitors are being launched.

Zero Bezel flush surfaced, new XX17 Series launched with MSR as peripheral. White & black color is available for this model ,comes with Accutouch (resistive) and iTouch (surface wave) technology.



1517L Black Color Bezel



1717L White Color

1517L & 1717L Specifications:		
Model	1517L	1717L
Display	15.0" diagonal, Active matrix TFT LCD	17.0" diagonal, Active matrix TFT LCD
Front Bezel	Zero Bezel	Zero Bezel
Color	White/Black	White / Black
Aspect Ratio	4:3 Standard	5:4 Standard
Useful Screen Area	Horizontal: 12.0" (304 mm) Vertical: 9.0" (228 mm)	Horizontal: 13.3" (338 mm) Vertical: 10.6" (270 mm)
Native (Optimal) Resolution	1024 x 768	1280 x 1024
Brightness	LCD panel: 250 nits with iTouch: 225 nits with AccuTouch: 200 nits	LCD panel: 250 nits with iTouch: 225 nits with AccuTouch: 200 nits
Response Time- Total	25msec	30msec
Viewing Angle	Horizontal: $\pm 80^\circ$ or 160° total Vertical: $\pm 70^\circ$ or 140° total	Horizontal: $\pm 85^\circ$ or 170° total Vertical: $\pm 80^\circ$ or 160° total
Contrast Ratio (Typical)	700:1	800:1
Input Video Format	Analog VGA	Analog VGA
Input Video Signal	Mini D-Sub 15-Pin VGA type	Mini D-Sub 15-Pin VGA type

Connector		
Touch Technology	IntelliTouch, AccuTouch	IntelliTouch, AccuTouch
Touch Interface	USB	USB
Power supply	External DC	External DC
Power Consumption	10W	21W
Stand	Tilt	Tilt
Monitor Dimensions (with Stand) (W x D x H)	14.1" (358 mm) x 6.8" (173 mm) x 12.5" (318 mm)	15.4" (392 mm) x 7.5" (191 mm) x 14.2" (360 mm)
Weight	4.1Kg	5.5kg
MTBF	50,000 hours demonstrated	50,000 hours demonstrated
Agency Approvals	Australia C-Tick, Canada cUL, IC, China CCC, Europe CE, Japan VCCI, Korea KCC, e-Standby, Mexico CoC, Taiwan BSMI Mark, United States UL, FCC, International CB RoHS, China RoHS, WEEE, IMERC	
Optional Peripherals	Magnetic Stripe Reader only.	

Two points touch options with flush surface: 1523L & 1723L

Compared with the above model, this one comes with more peripherals, not only MSR, RFID or additional second display or web camera. It accompanies with only itouch plus (dual points touch with fingers and flush surface) and with DVI input.



1523L & 1723L Specifications:

Model	1523LL	1723L
Display	15.0" diagonal, Active matrix TFT LCD	17.0" diagonal, Active matrix TFT LCD
Front Bezel	Zero Bezel	Zero Bezel
Color	White/ Black	White/ Black
Aspect Ratio	4:3 Standard	5:4 Standard
Useful Screen Area	Horizontal: 12.0" (304 mm) Vertical: 9.0" (228 mm)	Horizontal: 13.3" (338 mm) Vertical: 10.6" (270 mm)
Native (Optimal)	1024 x 768	1280 x 1024

Resolution		
Brightness	LCD panel: 250 nits with iTouch Plus: 225 nits	LCD panel: 250 nits with iTouch Plus: 225 nits
Response Time- Total	25msec	30msec
Viewing Angle	Horizontal: $\pm 80^\circ$ or 160° total Vertical: $\pm 70^\circ$ or 140° total	Horizontal: $\pm 85^\circ$ or 170° total Vertical: $\pm 80^\circ$ or 160° total
Contrast Ratio (Typical)	700:1	800:1
Input Video Format	Analog VGA, DVI-D	Analog VGA, DVI-D
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type, DVI-D connector	Mini D-Sub 15-Pin VGA type, DVI-D connector
Touch Technology	IntelliTouch Plus	IntelliTouch Plus
Touch Interface	USB	USB
Power supply	External DC	External DC
Power Consumption	12W	22W
Stand	Dual-position Stand with Tilt	Dual-position Stand with Tilt
Monitor Dimensions (with Stand) (W x D x H)	14.1" (358 mm) x 7.84" (199 mm) x 12.54" (318 mm)	15.4" (391 mm) x 8.24" (209 mm) x 14.2" (360 mm)
Weight	4.44Kg	5.21kg
MTBF	50,000 hours demonstrated	50,000 hours demonstrated
Agency Approvals	UL/cUL (*recognized component), FCC-A, Semko, CE, VCCI, C-Tick, China CCC	
Optional Peripherals	Magnetic Stripe Reader, Web Cam, RFID Reader, 0700L 7" Mounting Bracket Kit	



3243L Specifications: Dual touch tempered glass	
Model	3243L
Display	32" diagonal, Active matrix TFT LCD
Form Factor	Open-frame
Enclosure Color	Black
Aspect Ratio	16:9
Useful Screen Area	Horizontal: 27.5" (698 mm) Vertical: 15.4" (392 mm)
Native (Optimal) Resolution	1920 x 1080
Brightness	LCD panel: 350 nits with IntelliTouch Plus: 315 nits
Response Time- Total	6.5msec
Viewing Angle	Horizontal: $\pm 89^\circ$ or 178° total; Vertical: $\pm 89^\circ$ or 178° total
Contrast Ratio	3000:1
Input Video Format	Analog VGA, DVI video (<i>Asia and EMEA models without DVI</i>)
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type, DVI-D connector (<i>Asia and EMEA models without DVI</i>)
Touch Technology	IntelliTouch Plus
Touch Interface	USB
Power supply	Internal AC
Power Consumption	55W
Monitor Dimensions (W x D x H)	28.95" (735.4 mm) x 17.44" (443 mm) x 2.28" (58 mm)
Weight	12.3kg
MTBF	50,000 hours demonstrated
Agency Approvals	CB, UL, cUL ,FCC, CE, VCCI, IC, C-TICK, S-Mark, CCC, Russia & CIS GOST, NOM, KC, BSMI Argentina S-Mark; Australia C-Tick; Canada CUL, IC; China CCC; Europe CE; Japan VCCI; Korea KC, KCC, e-Standby; Mexico CoC; Russia GOST; Taiwan BSMI; United States UL, FCC; International CB; RoHS, China RoHS, WEEE IntelliTouch Plus screen: United States UL 60950 ball-drop

To help save the trouble of comparing the monitors, here is a quick check table for you.

		No Bezel	
<i>Standard aspect ratio 4:3 & 5:4</i>		VGA	VGA & DVI
No Bezel	Touch Technology	1515L 1715L	1517L 1717L
	AccuTouch	✓	✓
	IntelliTouch	✓	✓
	IntelliTouch Plus		✓
	Projected Capacitive	✓	
	APR	✓	
		Color: Dark Gray	Color: Black or White

		No Bezel	
<i>Wide aspect ratio 16:9</i>		VGA	VGA & DVI
	Touch Technology	1519L	1919L
	AccuTouch	✓	✓
	IntelliTouch	✓	✓
	IntelliTouch Plus		✓
	Projected Capacitive	✓	✓
	APR	✓	✓
		Color: Dark Gray	Color: Black

For further details on our products, please feel free to contact us
 @ (852) 25440899 or 25434921, or via email to sales@touchscreen.com.hk
 Marketing Department: Website: <http://www.touchscreen.com.hk>

If you want to unsubscribe to our newsletter, please inform us by a return email!